

PRESSWOOD PALLET

Model No.PS-1210-95-S4

PEFC / 16-44-917





Quality ControlISPM 15RecycleCost SavingImage: Cost Saving<

claire@penno-pallet.com | www.penno-pallet.com





TECHNICAL DATA SHEET 1200*1000mm











Specification

Model No.	PS-1210-95-S4
Dimension (MM)	1200*1000*139
Weight (KG)	16.5 ± 1.0 kg
Forklift Entry	Four-way
Loading Capacity*	2500 KGS (Dynamic)
	8000 KGS (STATIC)
Qty / Container	720 PCS / 20'GP
	1400 PCS / 40'HQ

Nestable

Saves your 70% valuable storage space and 50% transportation cost

Competitive Price

Almost half price for a new export pallet. An ideal alternative to conventional wooden pallets and expensive plastic pallets

ISPM15 Compliance - Export Approved

The manufacturing process of compress wood pallet takes place under high temperatures and pressure which exterminates bugs, infestation and eliminates the need for costly fumigation or heat treatment prior to export.

Safety Operation

Rounded corners and No-nail's or screw's design to prevent package from damage and help reduce employee injuries.



PENNO PACK-TECH CO.,LTD

No.4 Yangcheng Rd,Fengdu Industrial Zone,Pingyao Town, Yuhang District, Hangzhou, China, 311115 Mob:+8615088627233 TEL: +86 571 8873 1169 claire@penno-pallet.com | www.penno-pallet.com

